

Form PTO-1390 U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE (REV 10-95)		ATTORNEY'S DOCKET NUMBER 702-012058
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371		U.S. APPLICATION NO. 10/009105
INTERNATIONAL APPLICATION NO. PCT/NL00/00382	INTERNATIONAL FILING DATE 05.06.00 (June 05, 2000)	PRIORITY DATES CLAIMED 04.06.99 (June 04, 1999)
TITLE OF INVENTION DEVICE FOR SEPARATING A MIXTURE OF GAS WITH LIQUID AND/OR SOLID MATERIAL		
APPLICANT(S) FOR DO/EO/US Rombout Adriaan SWANBORN		
<p>Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:</p> <ol style="list-style-type: none"> <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371. <input checked="" type="checkbox"/> This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1). <input checked="" type="checkbox"/> A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2)) <ol style="list-style-type: none"> <input type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau). <input checked="" type="checkbox"/> has been transmitted by the International Bureau. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US). <input type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)). <input checked="" type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)) <ol style="list-style-type: none"> <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau). <input type="checkbox"/> have been transmitted by the International Bureau. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired. <input checked="" type="checkbox"/> have not been made and will not be made. <input type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). <input type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). <input type="checkbox"/> A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)). <p>Items 11. to 16. below concern document(s) or information included:</p> <ol style="list-style-type: none"> <input type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. <input checked="" type="checkbox"/> A FIRST preliminary amendment. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment. <input type="checkbox"/> A substitute specification <input type="checkbox"/> A change of power of attorney and/or address letter. <input checked="" type="checkbox"/> Other items or information: <ol style="list-style-type: none"> WO 00/74815-Front Page with Abstract, Specification, Claims and Drawings (25 pp.) Republished WO 00/74815 with International Search Report (4 pp.) International Preliminary Examination Report and Annex (9 pp.) 		

U.S. APPLICATION NO. 10/009105		INTERNATIONAL APPLICATION NO. PCT/NL00/00382		ATTORNEY'S DOCKET NUMBER 702-012058	
17. <input checked="" type="checkbox"/> The following fees are submitted: BASIC NATIONAL FEE (37 CFR 1.492(a)(1)-(5)): Search Report has been prepared by the EPO or JPO..... \$890.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) \$710.00 No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2))..... \$740.00 Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO..... \$1,040.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4)..... \$100.00 <div style="text-align: right;">ENTER APPROPRIATE BASIC FEE AMOUNT =</div>				CALCULATIONS PTO USE ONLY	
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input checked="" type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).				\$ 130.00	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	24 - 20	4	X \$18.00	\$ 72.00	
Independent claims	4 - 3 =	1	X \$84.00	\$ 84.00	
MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ \$280.00	\$ 0.00	
TOTAL OF ABOVE CALCULATIONS =				\$ 1,176.00	
Reduction of 1/2 for filing by small entity, if applicable. The above-identified applicants are entitled to claim Small Entity Status in the United States.				\$ 1,176.00	
SUBTOTAL =				\$ 1,176.00	
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$ 0.00	
TOTAL NATIONAL FEE =				\$ 1,176.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property				\$ 0.00	
TOTAL FEES ENCLOSED =				\$ 1,176.00	
				Amount to be: refunded	\$
				charged	\$
a. <input checked="" type="checkbox"/> A check in the amount of \$1,176.00 to cover the above fees is enclosed. b. <input type="checkbox"/> Please charge my Deposit Account No. _____ in the amount of \$ _____ to cover the above fees. A duplicate copy of this sheet is enclosed. c. <input checked="" type="checkbox"/> The Assistant Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. <u>23-0650</u> . A duplicate copy of this sheet is enclosed.					
NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.					
SEND ALL CORRESPONDENCE TO: Richard L. Byrne 700 Koppers Building 436 Seventh Avenue Pittsburgh, Pennsylvania 15219-1818 Telephone: (412) 471-8815 Facsimile: (412) 471-4094					
<div style="display: flex; align-items: center;"> <div> SIGNATURE Paul M. Reznick NAME 33,059 REGISTRATION NUMBER </div> </div>					

10/009105

JC10 Rec'd PCT/PTO 0 4 DEC 2001

PATENT APPLICATION/PCT
Attorney's Docket No. 702-012058

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of :

Rombout Adriaan SWANBORN :

International Application :
No. PCT/NL00/00382 :

International Filing Date :
05 June 2000 :

Priority Date Claimed :
04 June 1999 :

Serial No. Not Yet Assigned :

Filed Concurrently Herewith :

**DEVICE FOR SEPARATING A
MIXTURE OF GAS WITH LIQUID
AND/OR SOLID MATERIAL**

Pittsburgh, Pennsylvania
December 4, 2001

PRELIMINARY AMENDMENT

BOX PCT

Commissioner for Patents
Washington DC 20231

Sir:

Prior to initial examination, please amend the above-identified patent application
as follows:

IN THE SPECIFICATION:

On page 1 of the specification, amend the title to read as follows:

**DEVICE FOR SEPARATING A MIXTURE OF GAS
WITH LIQUID AND/OR SOLID MATERIAL**

**On page 1 of the specification after the title and before the first paragraph,
please insert the following section headings:**

BACKGROUND OF THE INVENTION

1. Field of the Invention

JC10 Rec'd PCT/PTO 0 4 DEC 2001

On page 1 of the specification before the second complete paragraph, please

insert the following section heading:

2. Description of the Related Art

On page 2 of the specification before the first complete paragraph, please

insert the following section heading:

SUMMARY OF THE INVENTION

On page 6 of the specification after the third complete paragraph, please

insert the following section heading:

BRIEF DESCRIPTION OF THE DRAWINGS

On page 7 of the specification before the first complete paragraph, please

insert the following section heading:

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

IN THE CLAIMS:

Original claims 1-25 were amended during Chapter II with a letter dated 03 August 2001. Please cancel all pending claims and rewrite them as new claims 26-49 as follows:

26. A device for separating a mixture of gas with liquid and/or solids, comprising a processing vessel comprising:

an inlet for a supply of the mixture to be separated;

a first and second outlet opening for a discharge of respectively a first mixture part and a second mixture part into a space of a further vessel;

a flow body arranged substantially concentrically in the processing vessel and provided with one or more swirl elements for setting the supplied mixture into swirling movement;

a discharge channel for discharging the first mixture part to the first outlet opening, which discharge channel is arranged substantially through an interior of the flow body and extends from a downstream side of the flow body to the first outlet opening;

a first resistance element with a predetermined flow resistance arranged between the second outlet opening and the flow body; and/or

a second resistance element with a predetermined flow resistance, arranged in the discharge channel, downstream of which the first outlet opening is arranged.

27. The device as claimed in claim 26, wherein the first resistance element includes one or more counter-swirl elements for reducing the swirling movement of the first mixture part flowing thereamong.

28. The device as claimed in claim 26, wherein the second resistance element includes one or more counter-swirl elements for reducing the swirling movement of the second mixture part flowing thereamong.

29. The device as claimed in claim 26, wherein the second resistance element includes a central core, on a top side of which is mounted a conical component which becomes wider in a flow direction.

30. The device as claimed in claim 29, wherein flat plates are provided for limiting a rotation of the mixture part flowing thereamong.

31. The device as claimed in claim 26, wherein the inlet opening of the processing vessel is provided with means for feeding in the mixture for separating at an increased tangential speed.

32. The device as claimed in claim 26, including a perforated plate placed close to the second outlet opening and downstream thereof for ensuring a substantially uniform velocity profile on a downstream side thereof.

33. The device as claimed in claim 26, wherein a swirl element includes one or more swirling blades, wherein the swirling blades are formed for setting into swirling movement or at least increasing the swirling movement of the mixture or mixture part flowing thereamong.

34. The device as claimed in claim 26, wherein a counter-swirl element includes one or more swirling blades, wherein the swirling blades are formed for decreasing the swirling movement of the mixture or mixture part flowing thereamong.

35. The device as claimed in claim 34, wherein an angle between a longitudinal direction of the processing vessel and a swirling blade amount to between approximately 0 and 80 degrees.

36. The device as claimed in claim 34, wherein the swirling blades are curved.

37. The device as claimed in claim 26, wherein the processing vessel includes an inner jacket which includes a conically tapering part in a flow direction.

38. The device as claimed in claim 37, wherein the conically tapering part is positioned between the swirl element and the resistance element.

39. The device as claimed in claim 26, wherein the first mixture part is formed by a light fraction, while the second mixture part is formed by a heavy fraction.

40. The device as claimed in claim 39, wherein the light fraction includes one or more gases and the heavy fraction includes one or more liquids.

41. The device as claimed in claim 39, wherein the light fraction comprises natural gas and the heavy fraction comprises oil and water.

42. The device as claimed in claim 26, wherein the first mixture part includes approximately 1% by volume of water and/or solids and the second mixture part includes at least approximately 95% by volume of liquid and/or solids.

43. The device as claimed in claim 26, wherein components of the processing vessel are embodied such that they can be fed through a manhole into a gravity separation vessel.

44. The device as claimed in claim 43, wherein a greatest dimension of a component amounts to a maximum of approximately 150 cm.

45. A device for separating a mixture of gas with liquid and/or solids, comprising:

a gravity separation vessel which is provided with an inlet for a supply of the mixture;

a processing vessel including:

an inlet for a supply of the mixture to be separated;

a first and second outlet opening for a discharge of respectively a first mixture part and a second mixture part into a space of a further vessel;

a flow body arranged substantially concentrically in the processing vessel and provided with one or more swirl elements for setting the supplied mixture into swirling movement;

a discharge channel for discharging the first mixture part to the first outlet opening, which discharge channel is arranged substantially through an interior of the flow body and extends from a downstream side of the flow body to the first outlet opening;

a first resistance element with a predetermined flow resistance arranged between the second outlet opening and the flow body; and/or

a second resistance element with a predetermined flow resistance, arranged in the discharge channel, downstream of which the first outlet opening is arranged,

the processing vessel can be mounted in the gravity separation vessel with the inlet connected to the inlet of the gravity separation vessel, wherein the first and second outlet openings of the processing vessel are arranged for the discharge of the first mixture part and the second mixture part into a space of the gravity separation vessel for further separation of the second mixture part.

46. The device as claimed in claim 45, wherein the second outlet of the processing vessel is placed at least partially in the second mixture part situated in the space so as to keep an open connection between the processing vessel and said space inside the separation vessel.

47. A method for treating a mixture of gas with liquid and/or solids, comprising the step of applying a device for separating a mixture of gas with liquid and/or solids, comprising a processing vessel comprising:

an inlet for a supply of the mixture to be separated;

a first and second outlet opening for a discharge of respectively a first mixture part and a second mixture part into a space of a further vessel;

a flow body arranged substantially concentrically in the processing vessel and provided with one or more swirl elements for setting the supplied mixture into swirling movement;

a discharge channel for discharging the first mixture part to the first outlet opening, which discharge channel is arranged substantially through an interior of the flow body and extends from a downstream side of the flow body to the first outlet opening;

a first resistance element with a predetermined flow resistance arranged between the second outlet opening and the flow body; and/or

a second resistance element with a predetermined flow resistance, arranged in the discharge channel, downstream of which the first outlet opening is arranged.

48. A method for designing a device for separating a mixture into a light and heavy fraction, comprising the step of designing components of a processing vessel such that the components can be fed through a manhole into a gravity separation vessel, wherein the processing vessel comprises an inlet for the mixture, a first outlet for the light fraction and a second outlet for the heavy fraction, in addition to rotation means for setting the mixture into rotation, wherein swirl elements arranged close to the inlet and/or counter-swirl elements arranged close to the first and second outlet are provided with swirling blades dimensioned such that through the desired degree of rotation a preselected pressure is available whereby the boundary surface between the heavy and light fraction extends on a preselected level within the processing vessel.

49. The method as claimed in claim 47, further including a gravity separation vessel which is provided with an inlet for a supply of the mixture, wherein the processing vessel can be mounted in the gravity separation vessel with the inlet connected to the inlet of the gravity separation vessel, wherein the first and second outlet openings of the processing vessel are arranged for the discharge of the first mixture part and the second mixture part into a space of the gravity separation vessel for further separation of the second mixture part.

ABSTRACT:

After the claims, please insert a page containing the Abstract Of The Disclosure, which is attached hereto as a separately typed page.

REMARKS

This Preliminary Amendment conforms the specification and the pending claims to customary United States practice.

Original claims 1-25 and amended claims 1-24 submitted during Chapter II have been canceled and rewritten as new claims 26-49 in order to eliminate the multiple dependencies and to bring the claims into conformance with standard United States patent practice.


An Abstract Of The Disclosure has been added as a separately typed page to be inserted after the claims.

Attached hereto is a marked-up version of the change made to the specification by the current amendment. The attachment is captioned "VERSION WITH MARKINGS TO SHOW CHANGES MADE".

Examination and allowance of claims 26-49 are respectfully requested.

Respectfully submitted,

WEBB ZIESENHEIM LOGSDON
ORKIN & HANSON, P.C.

By 
Paul M. Reznick, Reg. No. 33,059
Attorney for Applicant
700 Koppers Building
436 Seventh Avenue
Pittsburgh, PA 15219-1818
Telephone: 412/471-8815
Facsimile: 412/471-4094

THE UNIVERSITY OF CHICAGO

[AN APPARATUS AND METHOD FOR PROCESSING] DEVICE FOR SEPARATING A
MIXTURE OF GAS WITH LIQUID AND/OR SOLID MATERIAL

DEVICE FOR SEPARATING A MIXTURE OF GAS
WITH LIQUID AND/OR SOLID MATERIAL

ABSTRACT OF THE DISCLOSURE

Disclosed is a device for separating a mixture of gas with liquid and/or solids, which comprises a gravity separation vessel and a processing vessel which can be mounted in the gravity separation vessel. The processing vessel comprises a flow body which is provided with one or more swirl elements which set the feed mixture into rotation. The processing vessel also comprises a resistance element which is positioned between an outlet for the heavier fraction of the mixture and the flow body. The processing vessel may also comprise counter-swirl elements which are positioned in the discharge channel for the lighter fraction of the mixture.

10009105 050600

10/009105

WO 00/74815

5/PRTS
1

JC10 RECEIVED

0 4 DEC 2001

AN APPARATUS AND METHOD FOR PROCESSING OF A
MIXTURE OF GAS WITH LIQUID AND/OR SOLID MATERIAL

The present invention relates to an apparatus and method for processing of a mixture of gas with liquid and/or solid material.

Known are gravity separation vessels, also referred to as two or three phase separators, for separating mixtures of respectively gas with a liquid or gas with a light and a heavy liquid. As a result of the action of the force of gravity the gas is collected at the top of the gravity separation vessel, while the liquid is collected at the bottom of the vessel, wherein the light liquid remains floating on the heavy liquid. This provides the possibility of separating the mixture.

A device is also known which is constructed from a gravity separation vessel in which one or more inlet devices are arranged. With such inlet devices a pre-treatment can be carried out on the supplied mixture before the mixture is separated in the above described manner. Such inlet devices have as most important functions the reduction of the impact of the inlet flow so that the degree of separation inside the gravity separation vessel can be maximized, preventing liquid shattering whereby small liquid droplets could result which would make the separation process more difficult, and prevention of so-called "foaming", or the occurrence of foam.

These inlet devices have a number of drawbacks however. A first drawback is that since the liquids and the gases are discharged from different outlets, both outlets can have different pressure drops, with the result that gas can flow out of the liquid outlet and/or liquid out of the gas outlet. A second problem is that the discharge of gas can be obstructed by an increase in the quantity of liquid in the inlet device.

WO 00/74815

PCT/NL00/00382

2

The object of the present invention is to provide a device and method wherein the above stated drawbacks are obviated and wherein the liquid level is situated at a suitable height in the inlet device
5 (processing vessel).

According to a first aspect of the invention a device is provided for separating a mixture of gas with liquid and/or solids, comprising:

- a gravity separation vessel which is provided
10 with an inlet for the supply of the mixture;

- a processing vessel which can be mounted in the gravity separation vessel and connected to the inlet, which processing vessel comprises a first and second outlet opening for the discharge of respectively a first
15 mixture part and a second mixture part to a space of the gravity separation vessel for further separation of the second mixture part;

- a flow body arranged substantially concentrically in the processing vessel and provided with
20 one or more swirl elements for setting the supplied mixture into swirling movement;

- a discharge channel for discharging the first mixture part to the first outlet opening, which discharge channel is arranged substantially through the interior of
25 the flow body and extends from the downstream side of the flow body to the first outlet opening;

- a resistance element with a predetermined flow resistance arranged between the second outlet opening and the flow body. By setting the supplied
30 mixture into rotation a change in pressure can be realized in the processing vessel with which the pressure balance in the processing vessel can be preadjusted.

A device is per se known from European patent application EU 0436973 A2 wherein a supplied mixture of
35 gas with liquid and/or gas with solids is set into swirling movement in a vessel by a swirl element, which swirling generates centrifugal forces in the mixture whereby a first mixture part consisting substantially of

WO 00/74815

PCT/NL00/00382

3

liquid or solids is pressed against the wall of the processing vessel, while a second mixture part consisting substantially of gas moves to the middle of the processing vessel. The second mixture part is discharged in the known device via a discharge pipe at the top of the vessel, while the second mixture part is discharged via a discharge pipe at the bottom of the vessel. The known device is however of an entirely different type and is not suitable for carrying out a pretreatment in a gravity separation vessel in which the mixture parts, once they have been discharged, remain in open connection in (a space of) the gravity separation vessel for the purpose of a further treatment.

According to a preferred embodiment the device comprises one or more first counter-swirl elements arranged in the discharge channel for reducing the swirling movement of the first mixture part, downstream of which the first outlet opening is arranged. By arranging a counter-swirl element in the discharge channel to reduce the swirling movement of the first mixture part, the pressure drop over the discharge channel is decreased whereby the discharge of the first mixture part through the discharge channel is improved. This moreover prevents the first mixture part being entrained by the second mixture part and exiting to the outside through the second outlet opening.

According to a further preferred embodiment the resistance element comprises one or more second counter-swirl elements for reducing the swirling movement of the second mixture part. The pressure balance, and therewith the height of the second mixture part (liquid) in the processing vessel, can be further adjusted with the second counter-swirl element.

According to another aspect of the invention a device is provided for separating a mixture of gas with liquid and/or solids, comprising:

- a gravity separation vessel which is provided with an inlet for the supply of the mixture;

WO 00/74815

PCT/NL00/00382

4

- a processing vessel which can be mounted in the gravity separation vessel and connected to the inlet, which processing vessel comprises a first and second outlet opening for the discharge of respectively a first 5 mixture part and a second mixture part to a space of the gravity separation vessel for further separation of the second mixture part;

- a flow body arranged in the longitudinal direction of the processing vessel;

10 - a discharge channel for discharging the first mixture part which is arranged substantially through the interior of the flow body and extends from the downstream side of the flow body to the first outlet opening;

- a resistance element with a predetermined 15 flow resistance which is arranged between the second outlet opening and the flow body, wherein the resistance element comprises one or more counter-swirl elements. Using a resistance element embodied in such a manner the pressure in the processing vessel can be preadjusted to a 20 value which is appropriate under the conditions of use by a correct placing and dimensioning of the plates and the orientation thereof relative to each other.

The device preferably comprises one or more first counter-swirl elements arranged in the discharge 25 channel for reducing the swirling movement of the first mixture part, downstream of which the first outlet opening is arranged.

According to yet another aspect of the invention a device is provided for separating a mixture 30 of gas with liquid and/or solids, comprising:

- a gravity separation vessel which is provided with an inlet for the supply of the mixture;

- a processing vessel which can be mounted in the gravity separation vessel and connected to the inlet, 35 which processing vessel comprises a first and second outlet opening for the discharge of respectively a first mixture part and a second mixture part to a space of the

1009493 WO 00/74815

- a flow body arranged in the longitudinal direction of the processing vessel;

- According to a preferred embodiment a swirl element comprises one or more preferably curved swirling blades, wherein the swirling blades are formed for setting into swirling movement or at least increasing the swirling movement of the mixture or mixture part flowing therealong, while a counter-element preferably comprises one or more preferably curved swirling blades, wherein the swirling blades are formed for decreasing the swirling movement of the mixture or mixture part flowing therealong. Through a correct choice of the curvature the swirling speed of the mixture flowing therealong, and therewith the pressure drop over the swirl element, can be modified.

According to a further preferred embodiment the processing vessel comprises an inner jacket which comprises a conically tapering part in flow direction, in

WO 00/74815

PCT/NL00/00382

6

order to obtain a uniform flow of the first mixture part along the inner jacket.

According to a further preferred embodiment the components of the processing vessel are embodied such that they can be fed through a manhole in the gravity separation vessel. The greatest dimension of a component is herein a maximum of 150 cm. By constructing the processing vessel from such relatively small components it is possible to arrange the processing vessel in already existing gravity separators.

According to a further aspect of the present invention a method is provided for designing a separation vessel for separating a mixture into a light and heavy fraction, wherein the processing vessel comprises an inlet for the mixture, a first outlet for the light fraction and a second outlet for the heavy fraction, in addition to rotation means for setting the mixture into rotation, wherein swirl elements arranged close to the inlet and/or counter-swirl elements arranged close to the first and second outlet are provided with swirling blades dimensioned such that through the desired degree of rotation a pressure is available in the separation vessel for separating the mixture in as optimal a manner as possible.

By designing the rotation means or the counter-rotation means in correct manner in accordance with fluid dynamic principles the desired rotation of the mixture as well as the desired pressure drop over such a separation vessel can be preselected in accordance with the conditions, since the boundary surface between the heavy and light fraction extends in as optimal a manner as possible in the separation vessel.

Further advantages, features and details of the present invention will become apparent in the light of the following description of preferred embodiments thereof. Reference is made herein to the annexed drawings, in which:

WO 00/74815

PCT/NL00/00382

7

- figure 1 shows a partly cut-away perspective view of a gravity separator which is provided with two devices according to a preferred embodiment of the invention;
- 5 - figure 2 shows a partly cut-away perspective view of the preferred embodiment of figure 1;
- figure 3 shows a further elaborated perspective view of the preferred embodiment of figure 2;
- figure 4 shows a view in perspective of a
- 10 preferred embodiment of the counter-swirl element in the discharge channel;
- figure 5 shows a view in perspective of a preferred embodiment of the swirl element arranged concentrically in the processing vessel; and
- 15 - figure 6 shows a view in perspective of a preferred embodiment of a resistance element according to the invention.

Figure 1 shows a gravity separation vessel S much used in the offshore industry. Via a supply channel

20 t a mixture of gas and liquid is supplied in the direction of arrow a and then separated under the influence of gravity. The mixture is separated into a mixture part with a high gas content (light fraction) and a mixture part with a low gas content (heavy fraction).

25 Separation of the heavy fraction (water and oil) moreover occurs in a fraction with substantially water and a fraction with substantially oil, wherein the lighter oil remains floating on the heavier water. The separation of the layers of water and oil further takes place in a

30 manner known to the skilled person and in order to simplify the description is not further explained here.

In order to improve the operation of such (gravity) separation vessels, there are, as already stated above, inlet devices known in a number of

35 applications in the oil and gas-processing industry which carry out a pretreatment on the supplied mixture before further separating the mixture in known manner. Such inlet devices have as most important functions the

WO 00/74815

PCT/NL00/00382

8

reduction of the impact of the inlet flow so that the degree of separation inside the separating vessel S can be maximized, preventing liquid shattering whereby small liquid droplets could result which make the separating process more difficult, and prevention of so-called "foaming", or the occurrence of foam. A particular embodiment of inlet devices is formed by so-called inlet cyclones wherein the liquids and gases undergo a first separation under the influence of centrifugal forces generated in the inlet cyclone. The thus separated mixture parts come to lie in the remaining part of the gravity separation vessel S, wherein the heavy fraction is formed at the bottom of the vessel S and the light fraction at the top of the vessel S.

The mixture of liquid and gas supplied via supply tube t is guided into one of the inlet cyclones 1. In the shown embodiment two inlet cyclones 1 are arranged mutually adjacently. Embodiments are however also possible with only one inlet cyclone or with more than two inlet cyclones which are placed adjacently of each other or in other random order relative to each other. Arrow b in figure 1 indicates that the mixture flows to the right-hand inlet cyclone 1. The mixture could equally well flow to the left-hand inlet cyclone 1 and be treated in the same manner since the left-hand inlet cyclone is identical to the right-hand inlet cyclone. However, for the sake of clarity of the description only the operation of the right-hand inlet cyclone 1 will be described below.

The mixture enters inlet cyclone 1 (arrow b) in a chamber 2 which is formed from four parts which are provided with flanges 3 and fixed to each other using fixing means 4. The mixture subsequently flows (arrow c) downwards between a substantially cylindrical outer jacket 5 and a substantially cylindrical flow body 20 arranged concentrically relative to outer jacket 5. At one end the flow body 20 protrudes some distance into the space enclosed by outer jacket 5, while at the other end

WO 00/74815

PCT/NL00/00382

9

the flow body 20 extends up to an upper wall 22 of chamber 2.

On the outer surface of flow body 20 are arranged a number of curved swirling blades 25 which cause a swirling of the mixture flowing therealong.

Such a swirling blade 25 is constructed from a first part 25a, a second part 25b and a third part 25c which are formed such that a swirling blade 25 has an increasing curvature, i.e. the curvature of part 25b is greater than that of 25a, while the curvature of 25c is greater than that of 25b. The flowing mixture is hereby set into increasingly quicker rotation (arrow d).

As a result of the centrifugal forces the heavy fraction of the mixture, i.e. substantially liquid, is pressed against the inner side of outer jacket 5 and transported downward (arrow e) in the region along the outer jacket 5, while the light fraction of the mixture, i.e. substantially gas, comes to lie in the central region of the space enclosed by outer jacket 5 (arrow f).

Outer jacket 5 is provided with a flange 6 which connects onto a perforated jacket 7. Flange 6 also connects onto a conically tapering or funnel-shaped component 10 which is provided on the inner side with six vertical ribs 11.

The heavy fraction then enters a resistance element (arrow g) which decreases the swirling thereof and with which the pressure in the space enclosed by outer jacket 5 is increased. The embodiment of such a resistance element will be described at a later stage.

The heavy fraction subsequently flows from the underside through an exit opening to the outside and enters a tray-like component 9 which is fixed against the lower edge of the perforated jacket 7. The heavy fraction (v) then flows to the outside via the perforations in perforated plate 7 (arrow i, figure 1) and enters a part of the gravity separator 5 for a further separating treatment. A uniform velocity distribution of the heavy fraction exiting to the outside is effected by arranging

WO 00/74815

PCT/NL00/00382

10

such a perforated plate 7, which enhances the separation of the mixture of oil in water into a layer of water with oil floating thereon.

The pressure caused by resistance element 12 in the space enclosed by outer jacket 5 ensures that the light fraction is driven in the direction of arrow f into a discharge channel provided in the interior of flow body 20. The light fraction is then discharged in the direction of arrow h.

If however there is too great a pressure drop in the discharge channel it is possible that the gas, instead of being transported through the discharge channel, is entrained by the liquid flow (arrow e). This reduces the separating action of inlet cyclone 1.

In order to reduce the pressure drop in the discharge channel formed in flow body 20 a counter-swirl element is therefore arranged in the discharge channel.

Figure 4 shows a preferred embodiment of such a counter-swirl element 60. The light fraction flows through the discharge channel in the direction of arrow h, swirling in the meantime as a consequence of the above mentioned swirling blades 25. This swirling is impeded in that the light fraction is guided (arrow k in figure 3) along a counter-swirl element 60 formed by a number of swirling blades which each consist of a first swirling blade part 41 and a second swirling blade part 42, wherein swirling blade parts 41 and 42 make an angle α relative to the longitudinal axis of the discharge channel such that the initially rapidly swirling light fraction is gradually caused to swirl less rapidly. The angle α can vary in practice between 0 and 80 degrees, subject to the application.

The swirling blades are connected by means of a connecting piece 43 to upright plates 44 which are placed in substantially intersecting position relative to each other and which further limit the swirling movement of the light fraction. The pressure drop over the discharge

WO 00/74815

PCT/NL00/00382

11

channel is reduced by such a gradual decrease in the swirling movement of the light fraction.

The light fraction then exits to the outside (arrow j), and enters a part of the gravity separator 5 where further separation of the heavy fraction will take place.

Figure 6 shows a preferred embodiment of a resistance element, wherein for the sake of clarity the outer jacket 12 of the resistance element is omitted. The resistance element is constructed from a central core 50, on the top side of which is mounted a conical component 51 which becomes wider in the flow direction. A number of flat plates 52 extending in a fan shape in the length direction is moreover arranged on central core 50. These flat plates 52 limit the rotation of the mixture part flowing therealong in the direction of arrow 6, whereby a corresponding change in pressure occurs over the resistance element. The pressure balance in the processing vessel can hereby be adjusted.

In an embodiment which is not shown, a number of transverse plates are arranged on the outer jacket 12 and the longitudinal plates 52, this such that an opening is provided around core 50 along which liquid can flow. A transverse plate is moreover arranged on central core 50 which has a diameter such that between the peripheral edge thereof and outer jacket 12 there is an interspace along which the liquid can flow.

Owing to the above described construction the downward flowing heavy fraction will flow downward via the opening in the first transverse plate, the interspace between the second transverse plate and outer jacket 12 and the opening in the third transverse plate. With a correct embodiment of the openings, the number of plates, the form of the plates etc., the pressure above the resistance element, i.e. in the space enclosed by outer jacket 5, can be adjusted in advance as required.

The stated pressure must be high enough so that the light fraction is discharged through the discharge

WO 00/74815

PCT/NL00/00382

12

channel in the swirl element and low enough to prevent the liquid level in the inlet cyclone becoming too high, for instance beyond the underside of inner jacket 20, so that light fraction can no longer be discharged.

- 5 In an alternative embodiment (not shown) a resistance element is embodied as a counter-swirl element, whereby in similar manner as described with reference to the counter-swirl element in the discharge channel the pressure drop can be decreased. In this
- 10 embodiment the pressure in the space enclosed by inner jacket 5 can be adjusted by a predetermined correct dimensioning of the swirling blades, the curvature of the swirling blades, the number of swirling blades and so on.

- In another embodiment (not shown) the supply
- 15 tube t comprises a tangential inlet in inlet cyclone 1, i.e. the mixture entering inlet cyclone 1 already has a swirling movement. The swirling blades 25 for setting the mixture into a swirling movement can hereby be dispensed with.

- 20 All components of inlet cyclone 1 are formed and have small dimensions, for instance a maximum length or width of 1.5 m, such that they can be arranged in vessel S through manhole M (figure 1). The possibility is hereby created of arranging inlet cyclone 1 in processing
- 25 vessel S at any random stage. The operation of for instance separating vessels S already in use can thus be improved by later incorporating therein one or more inlet cyclones according to the invention.

- In addition to the use of the invention on
- 30 inlet cyclones in a gravity separator, many alternative applications can be realized which are all deemed to lie within the scope of the invention. It is for instance possible to incorporate a cyclone into an offshore pipeline, wherein the fluid flow supplied through the
- 35 pipeline is separated into a number of different fluid phases. It is also necessary in these alternative applications to avoid at all times the occurrence of a so-called "gas blowby", i.e. the exit of gas from the

WO 00/74815

PCT/NL00/00382

13

liquid outlet. If this takes place, the operation of the cyclone changes considerably: emulsion formation in the liquid phase or foam-forming in the liquid phase then result in a complete breakdown of the whole separator.

5 According to the invention all design parameters can be integrally optimized (inlet and both outlets), so that no high pressure drops need occur, which high pressure drops can cause emulsification of the liquid phase. Stated more generally, the pressure balance
10 over the gas/liquid surface in a rotating gas/liquid mixture can be predicted according to the invention such that the location of the gas/liquid surface can be adjusted as a function of throughput of the mixture, composition of the mixture, degree of rotation of the
15 mixture and the pressure drop over both outlets. Thus can be achieved that the liquid phase and gas phase flow out of the outlets intended for that purpose. The adjustment of the position of the surface takes place with rings of blades (which are situated either in the inlet section
20 whereby the degree of rotation is determined, or in the gas outlet whereby the pressure drop over the gas outlet section can be adjusted, or in a random combination of these locations).

 The degree of rotation of the mixture is
25 determined by providing the blades in the ring of blades in the inlet with a greater or smaller pitch. The stronger this rotation, the more the gas core in the mixture will tend to "creep" downward where it is precisely the liquid outlet which is situated.
30 Conversely, by arranging counter-blades in the liquid outlet not only is this rotation limited, but the pressure is also regained, which is exactly what can result in increased "gas-carryunder", i.e. gas slipping through in the liquid outlet. This can in turn be
35 prevented by doing the same in the gas outlet, where counter-blades can in principle realize a pressure recovery of the same order of magnitude and compensate the pressure build-up in the bottom of the cyclone with a

PCT/NL00/00382

comparable pressure build-up in the top of the cyclone. Thus is then achieved that the gas-liquid surface is held in the cyclone. This is a complicated design procedure which can only be performed successfully with high-
5 pressure flow models specifically validated in this field.

The present invention is not limited to the above described preferred embodiments thereof; the rights sought are defined by the following claims, within the scope of which many modifications can be envisaged.

1875

WO 00/74815

PCT/NL00/00382

15

CLAIMS

1. Device for separating a mixture of gas with liquid and/or solids, comprising:

- a gravity separation vessel which is provided with an inlet for the supply of the mixture;

5 - a processing vessel which can be mounted in the gravity separation vessel and connected to the inlet, which processing vessel comprises a first and second outlet opening for the discharge of respectively a first mixture part and a second mixture part to a space of the
10 gravity separation vessel for further separation of the second mixture part;

- a flow body arranged substantially concentrically in the processing vessel and provided with one or more swirl elements for setting the supplied
15 mixture into swirling movement;

- a discharge channel for discharging the first mixture part to the first outlet opening, which discharge channel is arranged substantially through the interior of the flow body and extends from the downstream side of the
20 flow body to the first outlet opening;

- a resistance element with a predetermined flow resistance arranged between the second outlet opening and the flow body.

2. Device as claimed in claim 1, comprising one
25 or more first counter-swirl elements arranged in the discharge channel for reducing the swirling movement of the first mixture part, downstream of which the first outlet opening is arranged.

3. Device as claimed in claim 1 or 2, wherein
30 the resistance element comprises one or more second counter-swirl elements for reducing the swirling movement of the second mixture part.

4. Device for separating a mixture of gas with liquid and/or solids, comprising:

WO 00/74815

PCT/NL00/00382

16

- a gravity separation vessel which is provided with an inlet for the supply of the mixture;
- a processing vessel which can be mounted in the gravity separation vessel and connected to the inlet,
- 5 which processing vessel comprises a first and second outlet opening for the discharge of respectively a first mixture part and a second mixture part to a space of the gravity separation vessel for further separation of the second mixture part;
- 10 - a flow body arranged in the longitudinal direction of the processing vessel;
- a discharge channel for discharging the first mixture part which is arranged substantially through the interior of the flow body and extends from the downstream
- 15 side of the flow body to the first outlet opening;
- a resistance element with a predetermined flow resistance which is arranged between the second outlet opening and the flow body, wherein the resistance element comprises one or more counter-swirl elements.
- 20 5. Device as claimed in claim 4, comprising one or more first counter-swirl elements arranged in the discharge channel for reducing the swirling movement of the first mixture part, downstream of which the first outlet opening is arranged.
- 25 6. Device for separating a mixture of gas with liquid and/or solids, comprising:
 - a gravity separation vessel which is provided with an inlet for the supply of the mixture;
 - a processing vessel which can be mounted in
 - 30 the gravity separation vessel and connected to the inlet, which processing vessel comprises a first and second outlet opening for the discharge of respectively a first mixture part and a second mixture part to a space of the gravity separation vessel for further separation of the
 - 35 second mixture part;
 - a flow body arranged in the longitudinal direction of the processing vessel;

WO 00/74815

PCT/NL00/00382

17

- a discharge channel for discharging the first mixture part arranged substantially through the interior of the flow body and extending from the downstream side of the flow body to the first outlet opening;
- 5 - one or more first counter-swirl elements arranged in the discharge channel for reducing the swirling movement of the first mixture part, downstream of which the first outlet opening is arranged;
- a resistance element with a predetermined
- 10 flow resistance arranged between the second outlet opening and the flow body.
7. Device as claimed in any of the foregoing claims, wherein a swirl element comprises one or more swirling blades, wherein the swirling blades are formed
- 15 for setting into swirling movement or at least increasing the swirling movement of the mixture or mixture part flowing therealong.
8. Device as claimed in any of the claims 1-6, wherein a counter-swirl element comprises one or more
- 20 swirling blades, wherein the swirling blades are formed for decreasing the swirling movement of the mixture or mixture part flowing therealong.
9. Device as claimed in claim 8, wherein the angle between the longitudinal direction of the
- 25 processing vessel and a swirling blade amount to between 0. and 80 degrees.
10. Device as claimed in claim 8 or 9, wherein the swirling blades are curved.
11. Device as claimed in any of the foregoing
- 30 claims, wherein the processing vessel comprises an inner jacket which comprises a conically tapering part 10 in flow direction.
12. Device as claimed in claim 11, wherein the conically tapering part is positioned between the swirl
- 35 element and the resistance element.
13. Device as claimed in at least one of the foregoing claims, wherein the first mixture part is

WO 00/74815

PCI/NL00/00382

18
formed by a light fraction, while the second mixture part is formed by a heavy fraction.

14. Device as claimed in claim 13, wherein the light fraction comprises one or more gases and the heavy fraction comprises one or more liquids.

15. Device as claimed in claim 14, wherein the light fraction comprises natural gas and the heavy fraction oil and water.

16. Device as claimed in any of the foregoing claims, wherein the first mixture part comprises 1% by volume of water and/or solids and the second mixture part at least 95% by volume of liquid and/or solids.

17. Device as claimed in any of the foregoing claims, wherein the components of the processing vessel are embodied such that they can be fed through a manhole into the gravity separation vessel.

18. Device as claimed in claim 17, wherein the greatest dimension of a component amounts to a maximum of 150 cm.

19. Device as claimed in any of the foregoing claims, wherein the processing vessel is placed at least partially in the second mixture part situated in the space.

20. Device as claimed in any of the foregoing claims, comprising a perforated plate placed close to the second outlet opening and downstream thereof for ensuring a substantially uniform velocity profile on the downstream side thereof.

21. Device as claimed in any of the foregoing claims, wherein the inlet opening of the processing vessel is provided with means for feeding in the mixture for separating at an increased tangential speed.

22. Processing vessel evidently intended for a gravity separation vessel as claimed in any of the foregoing claims.

23. Method for treating a mixture of gas with liquid and/or solids, wherein the device as claimed in any of the claims 1-21 is applied.

WO 00/74815

PCT/NL00/00382

19

24. Method for designing a separation vessel
for separating a mixture into a light and heavy fraction,
wherein the processing vessel comprises an inlet for the
mixture, a first outlet for the light fraction and a
5 second outlet for the heavy fraction, in addition to
rotation means for setting the mixture into rotation,
wherein swirl elements arranged close to the inlet and/or
counter-swirl elements arranged close to the first and
second outlet are provided with swirling blades
10 dimensioned such that through the desired degree of
rotation a pressure is available in the separation vessel
for separating the mixture in as optimal a manner as
possible.

25. Separating vessel designed in accordance
15 with the method as claimed in claim 24.

609959 5076934

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1

PCT

- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(57) Abstract: The present invention relates to a method for designing a separation vessel for separating a mixture into a light and heavy fraction, wherein the processing vessel comprises an inlet for the mixture, a first outlet for the light fraction and a second outlet for the heavy fraction, in addition to rotation means for setting the mixture into rotation, wherein swirl elements arranged close to the inlet and/or counter-swirl elements arranged close to the first and second outlet are provided with swirling blades dimensioned such that through the desired degree of rotation a pressure is available in the separation vessel for separating the mixture in as optimal a manner as possible, and to a separating vessel designed in accordance with the method of claim 24.

10/009105

WO 00/74815

PCT/NL00/00382

2 / 5




FIG. 2

10/009105

WO 00/74815

PCT/NL00/00382

3 / 5





FIG. 3

WO 00/74815

10/009105
PCT/NL00/00382

4 / 5

FIG. 4



WO 00/74815

10,009105
PCT/NL00/00382

5 / 5





FIG. 5



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of :
Rombout Adriaan SWANBORN : **DEVICE FOR SEPARATING A**
: **MIXTURE OF GAS WITH LIQUID**
International Application : **AND/OR SOLID MATERIAL**
No. PCT/NL00/00382 :
International Filing Date :
05 June 2000 :
Priority Date Claimed :
04 June 1999 :
Serial No. Not Yet Assigned :
Filed Concurrently Herewith :

Pittsburgh, Pennsylvania
December 4, 2001

LETTER RECOGNIZING ATTORNEYS

BOX PCT
Commissioner for Patents
Washington DC 20231

Sir:

Enclosed are appropriate papers for initiating the national phase of the above-identified PCT application, comprising a specification, claims and drawings. A Preliminary Amendment is also enclosed.

4 - Please accept the application for purposes of granting a filing date and recognize Richard L. Byrne, Russell D. Orkin, Paul M. Reznick and Jessica M. Schroth, Registration Nos. 28,498, 25,363, 33,059 and 47,102, respectively, as attorneys in this application, pending the filing of a formal Declaration and Power of Attorney.

Kindly direct all communications relating to this application to **Richard L. Byrne**.

Respectfully submitted,

WEBB ZIESENHEIM LOGSDON
ORKIN & HANSON, P.C.

By Paul M. Reznick
Paul M. Reznick, Reg. No. 33,059
Attorney for Applicant
700 Koppers Building
436 Seventh Avenue
Pittsburgh, PA 15219-1818
Telephone: 412/471-8815
Facsimile: 412/471-4094

Declaration and Power of Attorney For Patent Application

English Language Declaration

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

Device for separating a mixture of gas with liquid
and/or solid material
the specification of which

(check one)

☐ is attached hereto.

☒ was filed on June 5, 2000 as PCT international application xxx

~~Application Serial No.~~ No. PCT/NL00/00382 /

and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)			Priority Claimed	
<u>1012245</u> ✓ (Number)	<u>The Netherlands</u> ✓ (Country)	<u>June 4, 1999</u> ✓ (Day/Month/Year Filed)	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/> Yes	<input type="checkbox"/> No
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/> Yes	<input type="checkbox"/> No

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)

(Filing Date)

(Status)
(patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status)
(patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.


POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

William H. Logsdon	<u>22,132</u>	Barbara E. Johnson	<u>31,198</u>	Lester N. Fortney	<u>38,141</u>
Russell D. Orkin	<u>25,363</u>	Paul M. Reznick	<u>33,059</u>	Randall A. Notzen	<u>36,882</u>
David C. Hanson	<u>23,024</u>	John W. McIlvaine	<u>34,219</u>	Jesse A. Hirshman	<u>40,016</u>
Richard L. Byrne	<u>28,498</u>	Michael I. Shamos	<u>30,424</u>	James G. Porcelli	<u>33,757</u>
Frederick B. Ziesenheim	<u>19,438</u>	Blynn L. Shideler	<u>35,034</u>	Kent E. Baldauf, Jr.	<u>36,082</u>
Kent E. Baldauf	<u>25,826</u>	Julie W. Meder	<u>36,216</u>		

Send Correspondence to:

Russell D. Orkin, 700 Koppers Building, 436 Seventh Avenue, Pittsburgh PA 15219-1818

Direct Telephone calls to: (name and telephone number) Russell D. Orkin (412) 471-8815

Full name of sole or first inventor	
SWANBORN, Rombout Adriaan	
Inventor's signature	Date
	February 22, 2002
Residence	
Arnhem, The Netherlands NLX.	
Citizenship	
The Netherlands ✓	
Post Office Address	
Kemperbergerweg 39, NL-6818 RN Arnhem, The Netherlands	
Full name of second joint inventor, if any	
Second inventor's signature	Date
Residence	
Citizenship	
Post Office Address	

(Supply similar information and signature for third and subsequent joint inventors.)